

## Codis per a emprar amb la subscripció de notícies per RSS via Jabber: **JabRSS**

- `subscribe http://host.domain/path/to/file.rss[1]` .. subscribe to the given RSS URL
- `unsubscribe http://host.domain/path/to/file.rss[2]` .. unsubscribe from the given RSS URL
- `list` .. list currently subscribed RSS URLs (if a URL is marked with "error" it means that the last update of the RSS resource failed for some reason)
- `info http://host.domain/path/to/file.rss[3]` .. display some information about the given RSS URL
- `set plaintext` .. set the message type for headline notifications to normal/plain text
- `set chat` .. set the message type for headline notifications to chat/plain text
- `set headline` .. set the message type for headline notifications to headline (please note that not all Jabber clients support headline messages)
- `set also_deliver {Away} {XA} {DND}` .. also deliver headline messages when your presence is "Away", "Extended Away" or "Do Not Disturb"
- `set size_limit` .. limit the size of headline message to the specified amount of bytes
- `set store_messages` .. store at most the specified number of messages for later delivery (note that there is a hard limit of 48)
- `set header {Title} {url}` .. include an optional header line in headline notifications with the title and/or URL of the feed
- `set subject {Title} {url}` .. include an optional subject in headline notifications with the title and/or URL of the feed
- `configuration` .. displays your current configuration
- `show statistics` .. displays some basic server statistics
- `show usage` .. displays some basic usage statistics

Tret de: [http://dev.cmeerw.org/jabrss/Documentation<sup>\[4\]</sup>](http://dev.cmeerw.org/jabrss/Documentation)

---

<sup>[1]</sup> <http://host.domain/path/to/file.rss>

<sup>[2]</sup> <http://host.domain/path/to/file.rss>

<sup>[3]</sup> <http://host.domain/path/to/file.rss>

<sup>[4]</sup> <http://dev.cmeerw.org/jabrss/Documentation>